

HG laminate floor treating matrix

Treatment	Laminate
Protection against wear	P70
Regular cleaning	P71 P72 P73
Intensive cleaning, remove protective layer, pre-treatment protective layer	P74

HG®

floors

Laminate, vinyl and PVC protector



Protect

P70

Protects against scratching and wear
Adds a satin shine

1000 ml e

05136A1210006 2609

Products and tips? See:

HG.EU

Consumer Services?
Call: +44 (0)1279 598360

Attention: Transport and store the bottle upright. Keep in a frost-free area.

Medical personnel can request the data sheet via +31 36 54 94 777

The consumer's information sheet can be obtained via www.HG.eu

WARNING H226- Flammable liquid and vapour. **H319-** Causes serious eye irritation. **H336-** May cause drowsiness or dizziness. **EUH208-** Contains 2-methylisothiazol-3(2H)-one CAS 2682-20-4. May produce an allergic reaction. **P101-** If medical advice is needed, have product container or label at hand. **P102-** Keep out of reach of children. **P210-** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. **P233-** Keep container tightly closed. **P264-** Wash face, hands thoroughly after handling. **P271-** Use only outdoors or in a well-ventilated area. **P305+P351+P338-** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **P501-** Dispose of contents and container to a hazardous or special waste collection point. Contains: propan-2-ol; isopropyl alcohol; isopropanol CAS 67-63-0; <5% phosphates; Preservation agents: METHYLCHLOROISOTHIAZOLINONE (AND) METHYLISOTHIAZOLINONE; METHYLISOTHIAZOLINONE; BENZISOTHIAZOLINONE. Made in The Netherlands by HG International b.v., P.J. Oudweg 41, 1314 CJ Almere, The Netherlands, Tel.: +31 36 54 94 700



UFI: V9N4-MDPU-V004-RQYJ

50% RECYCLED PLASTIC BOTTLE

UK importer: HG UKI Ltd., Weston Business Centre, Parsonage Road, Takeley, Essex, CM22 6PU.
Tel.: +44 (0) 1206 822 744

HG laminate, vinyl and PVC protector (product 70)

- gives shine
- protects against wear, scratches and other damage

HG laminate, vinyl and PVC protector is a liquid polymer emulsion that is very easy to apply and leaves a glossy, wafer-thin but extremely strong protective coating once it has dried. This protects the top layer of the flooring against wear, scratches and other damage. This product also masks existing worn patches and gives an anti-slip effect.

Directions for use:

1. The surface, also for new flooring, must be completely clean and free of grease and dust. Remove any existing wax and polymer coatings. For the treatments that are required: see the HG treatment matrix on the side of this bottle.
2. Preferably apply with a waxer for even application (see the image on the front of this bottle). It is also possible to use a lint-free, clean (tea)towel wrapped around a squeegee.
3. Pour a small amount of the liquid undiluted over the floor and spread it thinly and evenly in a single direction without pressing down on the wax applicator or squeegee. Do not turn or polish!
4. Once the product has dried (after about 60 minutes), a second layer can be applied crosswise onto the first layer.
5. The floor can be walked on about 1 to 2 hours after the final treatment and has completely hardened after 3 days.

Coverage:

± 60 m² per litre per layer.

Attention:

This product should only be used on floors with completely glued seams. Do not use in rooms that may be damp, such as bathrooms.