HG terracotta floor treating matrix

Treatment	Terracotta
Removal of cement residue	P12
Application of basic protection (impregnation) / reducing porosity	P13
Protection of surface with (removable) polish	P84
Protection of surface with a wax layer	P82
Regular cleaning	P86
Intensive cleaning, remove protective layer, pre-treatment protective layer	P87
Oil and grease removal	P21 P42

8 711577 003890 >

05194A1210006 2608

Products and tips? See:
HG.EU
Consumer Services?
Call: +44 (0)1279 598360

HG®

floors

Terracotta cleaner

extra strong

Clean P87

Removes stubborn dirt and grease
Powerful and safe for floors

1000 ml e

Attention: Transport and store the bottle upright.
Medical personnel can request the data sheet via +31 36 54 94 777
The consumer's information sheet can be obtained via www.HG.eu

DANGER H314- Causes severe skin burns and eye damage. **EUH208-** Contains benzyl salicylate (118-58-1) (00063). May produce an allergic reaction. **P101-** If medical advice is needed, have product container or label at hand. **P102-** Keep out of reach of children. **P280-** Wear eye protection, protective gloves. **P301+P330+P331-** IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. **P303+P361+P353-** IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. **P305+P351+P338-** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **P501-** Dispose of contents and container to a hazardous or special waste collection point. Contains: D-Glucopyranose, oligomers, decyl octyl glycosides CAS: 68515-73-1; Sodium hydroxide; caustic soda CAS: 1310-73-2; <5% non-ionic surfactants, anionic surfactants; perfumes; BENZYL SALICYLATE; LINALYL ACETATE; LIMONENE; LINALOOL; PINENE.



Made in The Netherlands by HG International b.v.
P.J. Oudweg 41, 1314 CJ Almere, The Netherlands,
Tel.: +31 36 54 94 700

UFI: VV8A-HJRH-G00C-2P3G

50% RECYCLED PLASTIC BOTTLE

UK importer: HG UKI Ltd,
Weston Business Centre, Parsonage Road, Takeley,
Essex, CM22 6PU. Tel.: +44 (0) 1206 822 744

HG terracotta cleaner extra strong (product 87)

• removes stubborn dirt and grease

***HG terracotta cleaner extra strong* has been developed especially for the fast and easy removal of grease and ingrained dirt from all types of terracotta floors. It is also suitable for removing polish and other protective films, such as *HG terracotta protector (product 84)*.**

Directions for use:
For normal powerful cleaning: Dissolve half a litre in half a bucket (5 L) of lukewarm water and apply generously with a floor cloth or mop. Leave to work for a few minutes. Then scrub the surface well with a scrubbing brush or stiff broom, if necessary. Then remove the solution from the surface with a floor cloth or mop, regularly rinsing it in water and wringing it out. (A water extractor can be used if required.) Finally, mop the floor twice more with clean water. Repeat the treatment if necessary. To remove stubborn dirt or old polish or other protective films: Use this product undiluted. Follow the steps described above.

Usage:
±10-15 m^2 per litre undiluted.
±25-50 m^2 per litre diluted.

Maintenance:
For regular mopping: *HG terracotta cleaner shine restorer (product 86)*. See also the HG terracotta floors treatment matrix on the side of this bottle.