

HG floor tile treating matrix

Treatment	Porous tiles	Non-porous tiles	(High) gloss tiles
Removal of cement residue	P11 P12	P11 P12	P11
Application of basic protection (impregnation)/ reducing porosity	P13	-	-
Protection of surface against dirt and wear	P14	P14	-
Invisible protection against dirt and staining	P15	P15	-
Regular cleaning	P17	P16 P17	P18
Intensive cleaning, remove protective layer, pre-treatment protective layer	P20	P19 P20	P19 P20
Removal of oil and grease stains	P21 P42	P21	P21

HG®

floors

Tile cleaner extra strong



Clean

P20

Removes stubborn dirt and grease
Powerful and safe

1000 ml e

Attention: Transport and store the bottle upright.
Medical personnel can request the data sheet via
+31 36 54 94 777
The consumer's information sheet can be obtained
via www.HG.eu

DANGER H314- Causes severe skin burns and eye damage. **EUH208**- Contains benzyl salicylate (CAS: 118-58-1). May produce an allergic reaction. **P101**- If medical advice is needed, have product container or label at hand. **P102**- Keep out of reach of children. **P280**- Wear eye protection, protective gloves. **P301+P330+P331**- IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. **P303+P361+P353**- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. **P305+P351+P338**- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **P501**- Dispose of contents and container to a hazardous or special waste collection point. Contains: D-Glucopyranose, oligomers, decyl octyl glycosides CAS: 68515-73-1; Sodium hydroxide; caustic soda CAS: 1310-73-2; <5% non-ionic surfactants, anionic surfactants; perfumes; BENZYL SALICYLATE; LINALYL ACETATE; LIMONENE; LINALOOL; PINENE.



Made in The Netherlands by HG International b.v.
P.J. Oudweg 41, 1314 CJ Almere, The Netherlands,
Tel.: +31 36 54 94 700

UFI: GSQU-C7YY-J106-RU4V

50% RECYCLED PLASTIC BOTTLE

UK importer: HG UKI Ltd,
Weston Business Centre, Parsonage Road, Takeley, Essex,
CM22 6PU. Tel.: +44 (0) 1206 822 744

05435A1210006 2608

Products and tips? See:

HG.EU

Consumer Services?
Call: +44 (0)1279 598360



8 711577 013332 >

HG tile cleaner extra strong (product 20)

- also suitable for all types of natural stone

HG tile cleaner extra strong is a professional, extremely powerful cleaner for the removal of truly stubborn staining and wax, polish and other protective layers on floor tiles, flagstones and all types of natural stone types that are extremely difficult to remove. Also suitable for use with a scrubbing machine.

Directions:

For intensive soiling:

Dissolve half a litre in half a bucket (5L) of lukewarm water and apply generously to the floor surface with a floor cloth or mop. Do not treat more than 10 to 15 m² at once. Then scrub the surface well with a scrubbing brush or stiff broom, leave to penetrate for a few minutes and then scrub well again. Then remove the solution from the surface with a mop, regularly rinsing the mop and wringing it out in water. (A water extractor can be used if required.) After that, thoroughly mop the floor again 2 times with clean water.

For extremely strong and stubborn soiling or to remove very old polish and other protective films:

Dissolve 1 litre in a bucket of 4 litres of lukewarm water and then following the above steps.

For use with a scrubbing machine: Dissolve half a litre in 5 litres of water, depending on the intensity of the soiling.

Coverage:

± 35-70 m² per litre.

Attention:

Be careful not to splash paintwork, wood, metal, carpeting, etc. Sectioning off the area of the surface being cleaned very carefully with masking tape. If a white haze remains on the floor after the treatment, this indicates that the solution has not been completely removed. This white haze can be removed by mopping again with clean water.